TITLE

DIGITAL DATA DRIVER AND LCD USING THE SAME

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to data drivers, and more particularly, to a digital data driver and a liquid crystal display using the same.

Description of the Related Art

Conventionally, digital drivers of active matrix liquid crystal display (AMLCD) use storage registers (digital latches) as line buffers to store the digital video signal in line time and to drive the Digital to Analog Converter (DAC) in a line-at-a-time mode. Figs. 1A and 1B show the architecture of a conventional 6-bit digital data driver operating in line-at-a-time mode. According to this kind of architecture, the digital video data signals R[5]~B[0] are loaded into the first level corresponding latches (Latch11) by the enable signal from the shift register SRn during each horizontal scanning period. Thereafter, all video signals R[5]~B[0] stored in the first level latches (Latch11) are written to the second level latches (Latch12), and input to the DACs(DAC-Rn, DAC-Gn and DAC-Bn)simultaneously by the signal LB. According to the enable signal from the next shift register SRn+1, the digital video data signals R[5]~B[0] on the data lines at present are loaded into the first level corresponding latches (Latch21). Next, all video signals R[5]~B[0] stored in the first level latches (Latch21) are written to the second level latches (Latch22), and input to

the DACs (DAC-R$_{n+1}$, DAC-G$_{n+1}$ and DAC-B$_{n+1}$) simultaneously by the signal LB.   As resolution of AMLCD is increased the bit numbers of the data also increases such that the numbers of the digital data driver occupy a larger layout area.   In the conventional

5   arrangement, however, the high resolution AMLCD suffers from the limited lateral layout area in the digital data driver. Thus, when the resolution of the AMLCD is increased, layout difficulty in wire routing caused by additional latches and DACs.

10   ## SUMMARY OF THE INVENTION

It is therefore an object of the present invention to avoid layout difficulty in wire routing caused by increased lateral layout area because of an increase in LCD resolution.

According to the above mentioned object, the present

15   invention provides a digital data driver and an LCD that prevents layout difficulty in wire routing caused by increased lateral layout area because of an increase in LCD resolution, by sharing latches and DACs.

In the digital type data driver of the present invention,

20   a plurality of data lines, each transfer first data during a first period and second data during a second period.   A first shift register outputs a first enable signal during the first period, a second shift register outputs a second enable signal during the second period.   Transmission controllers are

25   coupled to the data lines respectively.   Each outputs the first data and the second data to two different DAC according to the first and second enable signals and two external signals as third and fourth enable signals.

In each transmission controller, first and second switching devices are connected in parallel, each has a first terminal coupled to one of the data lines and a second terminal coupled to an input terminal of the first latch. Third and fourth switching devices are connected in parallel, each has a first terminal coupled to an output terminal of the first latch and a second terminal coupled to an input terminal of the second latch. Fifth and sixth switching devices are connected in parallel, each has a first terminal coupled to an output terminal of the second latch and a second terminal coupled to an input terminal of the third latch. A seventh switching device has a first terminal coupled to an output terminal of the third latch and a second terminal coupled to an input terminal of the fourth latch. A first inverter has an input terminal coupled to the output terminal of the third latch.

The first and third switching devices are turned on to store the first data in the second latch according to the first enable signal, the second switching device is turned on to store the second data in the first switching device according to the second enable signal, the fifth switching device and the seventh switching device are turned on to output the first data to the first DAC according to the third enable signal, and the fourth switching device and the sixth switching device are turned on to output the second data to the second DAC through the first inverter according to the fourth enable signal.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention can be more fully understood by the subsequent detailed description and examples with reference made to the accompanying drawings, wherein:

5   Figs. 1A and 1B show the architectures of conventional digital data drivers;

Fig. 2 is a diagram of the LCD according to the present invention;

Fig. 3 is a diagram of the digital type data driver
10   according to the present invention;

Figs. 4A~4D show the operation of the transmission controller in the digital data driver according to the present invention;

Fig. 5 is a wave diagram of the transmission controller
15   according to the present invention; and

Fig. 6 shows the architecture of the digital data driver according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Fig. 2 shows a liquid crystal display 200 with a digital
20   data driver 203 of the present invention. As shown in Fig. 2, the liquid crystal display 200 has at least an active matrix region 201 consisting of a plurality of pixels, a scan driver 202, and a digital data driver 203. The scan driver 202 turns on one row of the pixels in the active matrix region 201
25   sequentially. The digital data driver 203 outputs data signals to corresponding pixels.

As shown in Fig. 3, the digital data driver 203 includes a plurality of data lines DL1~DLn, a plurality of shift

4

registers (SR_1 and SR_2), and a plurality of transmission controller TTC1~TTCn.

The plurality of shift registers output an enable signal sequentially. In this case, the first shift register SR1 outputs a first enable signal E_{n1} in the first period, and the second shift register SR_2 outputs a second enable signal En2 in the next period (the second period). The first period and the second period are in the same line period. Each of the data lines DL_1~DL_n transmits first data in the first period, and transmits second data in the second period. Each of the transmission controllers TTC1~TCCn is coupled to a corresponding data line.

In each transmission controller TTC1~TCCn, first and second switching devices T_1 and T_2 are connected in parallel, each has a first terminal coupled to one of the data lines DL1~DLn and a second terminal coupled to an input terminal of the first latch L1. Third and fourth switching devices T_3 and T_4 are connected in parallel, each has a first terminal coupled to an output terminal of the first latch L1 and a second terminal coupled to an input terminal of the second latch L2. Fifth and sixth switching devices T_5 and T_6 are connected in parallel, each has a first terminal coupled to an output terminal of the second latch L2 and a second terminal coupled to an input terminal of the third latch L3. A seventh switching device T_7 has a first terminal coupled to an output terminal of the third latch L3 and a second terminal coupled to an input terminal of the fourth latch L4, wherein the output terminal of the fourth latch L4 is coupled to the first digital to digital converter DAC1. A first inverter INV1 has an input

terminal coupled to the output terminal of the third latch
L3 and an output terminal coupled to the second DAC DAC2.

Figs. 4A~4D show the operation of the transmission
controller in the digital data driver according to the present
invention. Fig. 5 is a wave diagram of the transmission
controller according to the present invention. The operation
of the transmission controller in the digital data driver is
described above with reference to Figs 4A~4D and 5.

The first shift register SR1 outputs a first enable
signal E_{n1} in the first period of Nth display period, and the
first and switching device T_1 and T_3 are then turned on.
Consequently, the first data D0[0] on the data line DL0 is
stored in latches L1 and L2.

The second shift register SR_2 outputs a second enable
signal E_{n2} in the next period (second period) of the Nth display
period, and the first latch L1 is then turned on.
Consequently, the second data D0[1] on the data line DL0 is
stored into the latch L1.

Typically, there is a blanking period (blanking) between
the Nth display period and the Nth+1 display period.

The fifth and seventh switching devices T_5 and T_7 are
turned on according to a third enable signal E_{n3} from an
external circuit in a period (B1) of a blanking period. The
first data stored in the second latch L2 is then stored in
the third and fourth latch L3 and L4, and outputs to a first
DAC DAC1.

The fourth and sixth switching devices T_4 and T_6 are turned
on according to a fourth enable signal E_{n4} from an external
circuit in the next period (B2) of the blanking period. The
second data stored in the first latch L1 is then stored in

the second and third latch L2 and L3, and outputs to a second
DAC DAC1 through a first inverter INV1. In the present
invention, the operation of the transmission controllers
TCC2~TCCn is the same as the transmission controller TCC1 and
for the sake of brevity the operation of the transmission
controllers TCC2~TCCn is omitted here. Consequently, in the
present invention, the digital data driver 203 can output
digital data to the corresponding DACs DAC-R1~DAC-Rn,
DAC-G1~DAC-Gn and DAC-B1~DAC-Bn according to the output
signals from the shift registers SR_1~SR_n.

Therefore, the conventional digital data driver shown
in Figs. 1A and 1B can be replaced by the digital data driver
of the present invention, as shown in Fig. 6, wherein the
detailed circuit of the transmission controllers TCC1~TCCn
are the same as those shown in Fig. 3.

According to the architecture of the present invention,
the digital video data signals R[5]~B[0] (the first data) on
the data lines are loaded into the corresponding second
latches L2 by the enable signal from the shift register SR_n
in the first period of each horizontal scanning period. Next,
the digital video data signals R1[5]~B1[0] (the second data)
on the data lines are loaded into the corresponding first
latches L1 by the enable signal from the shift register SR_{n+1}
in the second period of each horizontal scanning period.
Thereafter, all the video signals R[5]~B[0] stored in the
second latches (L2) are written to the fourth latches (L4),
and input to the DACs (DAC-R_n, DAC-G_n and DAC-B_n) simultaneously
according to a third enable signal from an external circuit
in the period (B1) of the blanking period. Next, all the video
signals R1[5]~B1[0] stored in the first latches (L1) are

7

written to the third latches (L3), and input to the DACs ($DAC\text{-}R_{n+1}$, $DAC\text{-}G_{n+1}$ and $DAC\text{-}B_{n+1}$) simultaneously through inverters according to a fourth enable signal from the external circuit in the nest period (B2) of the blanking period.

Therefore, by sharing latches and DACs, the digital data driver and LCD of the present invention prevents layout and wire routing difficulties caused by the increased lateral layout required by the increase in LCD resolution.

While the invention has been described by way of example and in terms of the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. To the contrary, it is intended to cover various modifications and similar arrangements (as would be apparent to those skilled in the art). Therefore, the scope of the appended claims should be accorded the broadest interpretation so as to encompass all such modifications and similar arrangements.